



**TILE ROOFING  
INSTITUTE**

**FRSA/TRI 5<sup>th</sup> Edition Self Adhered Cap Sheet Submittal Form**

Manufacturer: INTERWRAP INC Product Submitted (one per submittal) TITANIUM TWO PLY UDL SYSTEM (PSU30/UDL30)

We endorse that the product listed above meets all of the following testing standards:

- TAS 103
- ASTM D 1970, section 7.9 (satisfies nail seal-ability)
- ASTM D 4798, U.V. Exposure, minimum 90 days
- Underlayment thickness, minimum 40mils

Company Representative: E. LOZANO Job Title: CAO Date: APRIL 21/11

**Product Usage Provisions**

We endorse the product listed above for the following roof tile application methods:

	Yes	No
Mechanically Fastened	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Adhesive Set	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Mortar Set	<input type="checkbox"/>	<input checked="" type="checkbox"/>

- (A) Is the warranty of the product listed above affected by the use of a sealed attic system? Yes  No
- (B) Is the warranty of the product listed above limited by the type of decking utilized? Yes  No

\*if answering yes to either question, please provide detailed explanation or attach copy of warranty detailing limitations

(A) Will be reviewed case by case basis.  
(B) Refer to Installation guidelines of Titanium PSU30/UDL30.  
Follow the local municipality or regional codes as applicable.

Company Representative: EDUARDO LOZANO Job Title: CAO Date: APRIL 21/11

Note: The existing standards for #30lb base sheets as well as #90 and modified caps sheets (SBS/APP) will not change