

FRSA/TRI 5th Edition Self Adhered Cap Sheet Submittal Form

Manufacturer: MFM Building Products Corp. Product Submitted (one per submittal)
STS Underlayment

We endorse that the product listed above meets all of the following testing standards:

- TAS 103
- ASTM D 1970, section 7.9 (satisfies nail seal-ability)
- ASTM D 4798, U.V. Exposure, minimum 90 days
- Underlayment thickness, minimum 40mils

Company Representative: Whit Croft Job Title: Technical Service Manager Date: September 8, 2010

Product Usage Provisions

We endorse the product listed above for the following roof tile application methods:

Yes- Mechanically Fastened

Yes- Adhesive Set

No - Mortar Set

Yes- The warranty of the product listed above affected by the use of a sealed attic system?

Yes- The warranty of the product listed above limited by the type of decking utilized?

*if answering yes to either question, please provide detailed explanation or attach copy of warranty detailing limitations:

If STS Underlayment is installed as a complete deck covering it will act as a vapor barrier; proper and adequate attic ventilation is required.

When installing STS Underlayment to OSB and/or dens-deck it must be primed with an approved asphalt base primer.

Company Representative: Whit Croft Job Title: Technical Service Manager Date: September 8, 2010

Note: The existing standards for #30lb base sheet as well as #90 and modified caps sheets (SBS/APP) will not change