



TILE ROOFING INSTITUTE

FRSA/TRI 5th Edition Self Adhered Cap Sheet Submittal Form

Manufacturer: POLYGLASS USA Product Submitted (one per submittal) POLYFLEX SA P

We endorse that the product listed above meets all of the following testing standards:

- TAS 103
ASTM D 1970, section 7.9 (satisfies nail seal-ability)
ASTM D 4798, U.V. Exposure, minimum 90 days
Underlayment thickness, minimum 40mils

Company Representative: JAMES ARNOLD Job Title: TECHNICAL SVS MGR Date: 9-30-10

Product Usage Provisions

We endorse the product listed above for the following roof tile application methods:

Table with 2 columns: Yes, No. Rows: Mechanically Fastened, Adhesive Set, Mortar Set.

Is the warranty of the product listed above affected by the use of a sealed attic system? Yes No

Is the warranty of the product listed above limited by the type of decking utilized? Yes No

\*if answering yes to either question, please provide detailed explanation or attach copy of warranty detailing limitations

SEE ATTACHED TECHNICAL BULLETINS ON APPROVED SUBSTRATES AND SEALED ATTIC SYSTEMS

Company Representative: JAMES ARNOLD Job Title: TECHNICAL SVS MGR Date: 9-30-10

Note: The existing standards for #30lb base sheet as well as #90 and modified caps sheets (SBS/APP) will not change