



TILE ROOFING
INSTITUTE

FRSA/TRI 5th Edition Self Adhered Cap Sheet Submittal Form

Manufacturer: POLYGLASS USA Product Submitted (one per submittal) TILE PRO

We endorse that the product listed above meets all of the following testing standards:

- TAS 103
- ASTM D 1970, section 7.9 (satisfies nail seal-ability)
- ASTM D 4798, U.V. Exposure, minimum 90 days
- Underlayment thickness, minimum 40mils

Company Representative: JAMES ARNOLD Job Title: TECHNICAL SYS MGR Date: 9-30-10

Product Usage Provisions

We endorse the product listed above for the following roof tile application methods:

	Yes	No
Mechanically Fastened	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Adhesive Set	<input type="checkbox"/>	<input type="checkbox"/>
Mortar Set	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Is the warranty of the product listed above affected by the use of a sealed attic system? Yes No

Is the warranty of the product listed above limited by the type of decking utilized? Yes No

*if answering yes to either question, please provide detailed explanation or attach copy of warranty detailing limitations

SEE ATTACHED TECHNICAL BULLETINS ON
APPROVED SUBSTRATES AND SEALED ATTIC
SYSTEMS

Company Representative: JAMES ARNOLD Job Title: TECHNICAL SYS MGR Date: 9-30-10

Note: The existing standards for #30lb base sheet as well as #90 and modified caps sheets (SBS/APP) will not change